



Fitted lamp Beltrolux W

Application:

Kits for all kinds of copying equipment and manufacture.

Models supplied with 3000 W, 5000 W or 6000 W.



Design:

The BELTROLUX D lamp operates without shutter.

An instant start control makes sure that the lamp must not be heated and the maximal spectral range is available from the very beginning at each start. A re-start of the lamp is available at once. The special high energy reflector enables a perfect and even exposure. By eliminating the stand-by-periods and together with the specially designed uv reflector an energy saving of up to 80% could be achieved. Only ecologically beneficial lamps are utilized. All operational sequences are controlled by the specially designed control computer BELTROMAT 8100. Of course BELTRON also disposes free-of-charge used lamps from it's customers.

Technical Information Fitted lamp Beltrolux W

Standard models:

MH-copy lamps for horizontal exposure

Art.-No.:	Description:	Lamp power:
49.227	Beltrolux 3000 D / 3000 W	3000 W
49.228	Beltrolux 5000 D / 5000 W	5000 W
49.252	Beltrolux 6000 D / 6000 W	6000 W



Fitted lamp Beltrolux W

Application:

Kits for all kinds of copying equipment and manufacture.

Models supplied with 3000 W, 5000 W or 6000 W.



Technical Information Fitted lamp Beltrolux W

Standard models:

MH-copy lamps for vertical exposure

Art.-No.:	Description:	Lamp power:
49.225	Beltrolux 3000 D / 3000 W	3000 W
49.226	Beltrolux 5000 D / 5000 W	5000 W
49.251	Beltrolux 6000 D / 6000 W	6000 W

Standard models:

MH-copy lamps for mounting kits in devices

Art.-No.:	Description:	Lamp power:
49.232	Beltrolux 3000 D / 3000 W	3000 W
49.233	Beltrolux 5000 D / 5000 W	5000 W
49.253	Beltrolux 6000 D / 6000 W	6000 W

Beltron GmbH



Fitted lamp Beltrolux W

Application:

Kits for all kinds of copying equipment and manufacture.

Models supplied with 3000 W, 5000 W or 6000 W.



Technical Information Fitted lamp Beltrolux W

Options:

Art.-No.:	Description:
59.067	overhead mounting brackets, complete hand winch with closure (for horizontal exposure)
59.042	movable stand, for all copy lamps to exposure vertically
59.068	impulse counter to show the succeeded exposures
60.055	extra price for special connecting voltage
48.006	Control computer BELTROMAT 815 / Control computer BELTROMAT 8100
59.011	UV photocell

Starebulbs (Gallium):

MH-copy lamps for vertical exposure

Art.-No.:	Description:	Lamp power:
28.127	Direktstrahler	1000 W
28.124	Direktstrahler	3000 W
28.122	Direktstrahler	5000 W
28.182	Direktstrahler	6000 W

The Fitted lamp Beltrolux W is used successfully in:
printing industry, electronic industry, packaging industry, automotive industry and glass industry.

These are just a few examples from the various partner portfolio of Beltron.

Beltron GmbH

Siemensstraße 6 | D-63322 Rödermark | Phone: +49 6074 89199-0 | info@beltron.de | www.beltron.de